

## Waterproof ExStik® II pH/Conductivity Meter

- ✓ **Combination rugged Flat Surface pH electrode**
- ✓ Innovative design with flat surface technology for quick on-the-spot pH measurements combined with autoranging high accuracy Conductivity cell

### Features:

- Measures 5 parameters including Conductivity, TDS, Salinity, pH, and Temperature using one electrode
- 9 units of measure: pH,  $\mu\text{S}/\text{cm}$ ,  $\text{mS}/\text{cm}$ , ppm, ppt, mg/L, g/L, °C, °F
- Analog bargraph indicates trends
- Memory stores up to 25 labeled readings
- Adjustable Conductivity to TDS ratio from 0.4 to 1.0; 0.5 fixed Salinity ratio
- RENEW feature alerts user when electrode needs replacement
- Auto power off and low battery indicator
- Waterproof to IP57
- EC500 meter includes electrode, protective sensor cap, sample cup with cap, four 3V CR-2032 batteries, and 48" (1.2m) neckstrap.
- Order **Conductivity standards and pH buffers separately**
- EC510 Kit includes EC500, 84 $\mu\text{S}/\text{cm}$ , 1413 $\mu\text{S}/\text{cm}$ , 12880 $\mu\text{S}/\text{cm}$  Conductivity calibration standards, pH buffer pouches (1 each of 4, 7, 10pH plus rinse solution), weighted base, 3 sample cups with caps, and case — \$19 Savings



Combination flat surface pH electrode with Conductivity cell



Specifications	Range	Max Resolution	Basic Accuracy
Conductivity	0 to 199 $\mu\text{S}/\text{cm}$ , 200 to 1999 $\mu\text{S}/\text{cm}$ , 2.00 to 19.99 $\text{mS}/\text{cm}$	0.1 $\mu\text{S}/\text{cm}$	±2%FS
TDS/Salinity	0 to 99.9ppm (mg/L), 100-999ppm (mg/L)	0.1 ppm (mg/L)	±2%FS
pH	0.00 to 14.00 pH	0.01 pH	±0.01 pH
Temperature	23° to 194°F (-5 to 90°C)	0.1°F/°C	±1.8°F/1°C
Waterproof	IP57		
Memory	25 datasets		
Dimensions	1.4 x 7.3 x 1.6" (36 x 185 x 41mm)		
Weight	3.8oz (110g)		

### Ordering Information:

- EC500 ..... Waterproof ExStik® II pH/Conductivity Meter  
 EC510 ..... Waterproof ExStik® II pH/Conductivity Meter Kit  
 EC505 ..... Spare ExStik® II pH/Conductivity cell module for EC500  
 EC-84-P ..... 84 $\mu\text{S}$  Conductivity Standard (2 bottles - 1 pint each)  
 EC-1413-P ..... 1413 $\mu\text{S}$  Conductivity Standard (2 bottles - 1 pint each)  
 PH4-P ..... pH 4 Buffer Solution (2 bottles - 1 pint each)  
 PH7-P ..... pH 7 Buffer Solution (2 bottles - 1 pint each)  
 PH10-P ..... pH 10 Buffer Solution (2 bottles - 1 pint each)

