

## TP 28 1300

**Type** TP 28 1300



### Scope of delivery

- Test certificate
- Mains cable
- Insert exchange tool
- Operating manual

### Optional accessories

- Transport case
- Adapter sleeve
- PC software
- PC cable
- DKD certificate
- Works certificate

Technical data	
<b>Type</b>	TP 28 1300
<b>Control sensor</b>	Internal
Micro Bath	
<b>Temperature range</b>	
<b>Tolerance</b>	
<b>Stability</b>	
<b>Measurement zone</b>	
Dry block	
<b>Temperature range</b>	400...1300 °C
<b>Tolerance</b>	±2 °C
<b>Stability</b>	±0.5 °C
<b>Measurement zone</b>	at 200 mm
Infrared	
<b>Temperature range</b>	
<b>Tolerance</b>	
<b>Stability</b>	
<b>Measurement zone</b>	
Surface	
<b>Temperature range</b>	
<b>Tolerance</b>	
<b>Stability</b>	
<b>Measurement zone</b>	
Block	
	Ø 28 mm / depth 200 mm
Display	
<b>Display</b>	1-line, 4½-digit display Red, unit °C (°F optional)
<b>Display range</b>	0...1300 °C
<b>Resolution</b>	0.5 °C
General data	
<b>Dimensions</b>	
→ Width	510 mm
→ Height	290 mm
→ Depth	415 + 100 mm
<b>Weight</b>	Approx. 25 kg
<b>Power supply</b>	230 VAC, 50 / 60 Hz
<b>Power consumption</b>	Approx. 1000 VA