

PRINCIPAL TEMPERATURE TRANSMITTER LINE

IPAQ C/R 202



This low-cost, 3-wire Pt100 RTD input with programmable output transmitter is an excellent value. Digital design provides long-term stability and excellent accuracy. Excellent alternative to analog transmitters.

Input: Pt100 RTD
Accuracy: $\pm 0.10\%$ of Span
Approvals: ATEX & IECEx (C202X)
Sensor and System Error Correction Capability

^{MIN}IPAQ-HLP/L



The ^{MIN}IPAQ is a cost-competitive, non-isolated temperature transmitter that will accept RTD and thermocouple inputs. This transmitter is programmable via a PC.

Input: RTD, T/C
Accuracy: $\pm 0.15\%$ of Span
Sensor and System Error Correction Capability

IPAQ C/R 330



The 330 is our latest universal input, isolated, PC-programmable transmitter offers superior accuracy and lifetime performance.

Input: RTD, T/C, Ω , mV
Accuracy: $\pm 0.08\%$ of Span
Approvals: ATEX & IECEx (C330X) / FM & CSA (Pending)
Sensor and System Error Correction Capability & 50-point Custom Linearization

IPAQ C/R 530



New HART® transmitter developed to meet the highest standards of accuracy and reliability. The 530 offers NFC and Bluetooth® wireless configuration capabilities.

Input: RTD, T/C, Ω , mV
Accuracy: $\pm 0.08\%$ of Span
Approvals: ATEX & IECEx (C330X) / FM & CSA (Pending)
Sensor and System Error Correction Capability & 50-point Custom Linearization

ICON Lite Kit



For configuration of:

- C/R 202
- ^{MIN}IPAQ-HLP/L
- C/R 330
- C/R 520
- C/R 530

Configure INOR transmitters listed above with this ICON Lite Kit – it includes the USB Interface, PC→Interface and Interface→Transmitter cables

INOR Wireless Configuration



INOR Connect®
Home Screen

Configuration
Screen

Bluetooth
Connectivity

NFC / Near Field
Communication

Check out INOR's Wireless Concept at

<http://inor.com/products/inor-connect/>