

LPU-2127 Loop Powered Ultrasonic Level Sensor



Flexible by Design

With a built in keypad for easy programming and flexibility, the LPU-2127 provides continuous level/distance measurement you can count on. Its durability, range, and simplicity make it a great sensor for many applications.

Features

- 1 - 25 ft. (0.3 - 7.6 m) detection range on liquids
- 1 - 10 ft. (0.3 - 3 m) detection range on solids
- Loop powered 4-20 mA output
- Integrated keypad and LCD display

W. H. Cooke & Co., Inc.

Manufacturer of thermocouples & RTD's Made in the USA
Supplier of industrial controls, heaters, and sensors since 1963

sales@whcooke.com

717-630-2222

LPU-2127 Specifications



Performance

- Operating Range
 - 1 - 25 ft. (0.3 - 7.6 m) on liquids
 - 1 - 10 ft. (0.3 - 3 m) on solids
- Beam Pattern: 90° off axis
- Internal Temperature Compensation
- Frequency: 69 kHz
- Accuracy: ±0.25% of detected range
- Resolution: 0.1 in. (2.5 mm)
- Response Time: Output dependent on output ranges from 0.6 - 3 seconds

Connectivity

- Output:
 - 4-20 mA (loop-powered)
 - 600 ohms @ 24 VDC
 - 150 ohms @ 12 VDC

Environmental

- Ratings: IP65
- Operating Temp: -40° - 140°F (-40° - 60°C)

Certification

- CSA C/US: Class 1, Div. 2, Groups C & D
- CSA C/US: Class 1, Zone 2, AEx nA IIB T6

Electrical

- Cable Connection: 2-terminal connector
- Total Current Draw: 4-20 mA
- Supply Voltage: 12-28 VDC

Programming

- Integrated keypad and LCD display

Physical

- PVDF (Kynar®) transducer housing
- PET upper housing
- Transducer Type: Ceramic, PVDF face



Options

LPU-2127

W. H. Cooke & Co., Inc.

sales@whcooke.com

Manufacturer of thermocouples & RTD's Made in the USA
Supplier of industrial controls, heaters, and sensors since 1963

717-630-2222